

VERTICAL PRESSURE STEAM STERILIZER (Digital Display Automation)

Characteristics:

1. Fully stainless steel structure
2. Hand wheel type of quick-open door structure
3. Door safety lock system
4. Digital display of working status, touch of key
5. Auto discharge the cool air, and steam discharging auto matically after sterilization
6. Over temperature & over pressure auto-protection
7. Safe protection of water lacking
8. Self-inflating type seal
9. Automatically shut off with beep reminding after sterilization
10. Used for sterilization of medical instruments, medical cotton products.
11. Fully stainless steel SUS304/AISI 304 -3mm
12. 24 months warranty
13. Possible to install drying system according request



Technical Data:

Model technical data	LS-35HD(automatic)	LS-50HDI(automatic)	LS-75HD(automatic)	LS-100HD(automatic)
Chamber volume	35L(φ318×450)mm	50L(φ340×550) mm	75L(φ400×600) mm	100L(φ440×650) mm
working pressure	0.22MPa			0.14 MPa
Working temperature	134℃			126℃
Max working pressure	0.23 Mpa			0.165 Mpa
Heat average	≤±1℃			
Timer	0~99min or 0~99hour59min			
Adjustment of temperature	105~134℃		105~126℃	
Power	2.5Kw/AC220V.50Hz	3Kw/AC220V.50Hz	4.5Kw/AC220V.50Hz	
Overall dimension	450×450×1010(mm)	510×470×1130(mm)	560×560×1120 (mm)	540×560×1250 (mm)
Transport dimension	570×550×1150(mm)	590×590×1280(mm)	650×630×1280(mm)	680×630×1370(mm)
G.W/N.W	72Kg/56Kg	88Kg/ 68Kg	100Kg/ 80Kg	110Kg/ 85Kg